

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	13/02/2023	Time Survey completed:	13:04
Survey address:	Buckhaven, Fife KY8		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY57271744	24/01/2023
Probe	Agos Aria-6000 Antenna	60001089	28/11/2022
Cabling	1.7m Cable	1274	28/11/2022

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

Notes

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

** All other frequencies between 420 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

Location 1

Measurement time:	12:20
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.01408
800 MHz	0.07105
900 MHz	0.05350
1400 MHz	0.00045
1800 MHz	0.00148
1900 MHz	0.00020
2100 MHz	0.04849
2300 MHz	0.00684
2600 MHz TDD	0.00033
2600 MHz FDD	0.00010
3.4 GHz	0.00107
3.8 GHz	0.00258
Others	0.05472
Total	0.25489

Location 2

Measurement time:	12:27
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.01912
800 MHz	0.10963
900 MHz	0.04737
1400 MHz	0.00045
1800 MHz	0.00487
1900 MHz	0.00021
2100 MHz	0.01916
2300 MHz	0.01334
2600 MHz TDD	0.00034
2600 MHz FDD	0.00010
3.4 GHz	0.00113
3.8 GHz	0.00271
Others	0.05719
Total	0.27562

Location 3

Measurement time:	12:34
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.01026
800 MHz	0.05922
900 MHz	0.03862
1400 MHz	0.00046
1800 MHz	0.00095
1900 MHz	0.00021
2100 MHz	0.01591
2300 MHz	0.00833
2600 MHz TDD	0.00035
2600 MHz FDD	0.00010
3.4 GHz	0.00117
3.8 GHz	0.00281
Others	0.05803
Total	0.19642

Location 4

Measurement time:	12:43
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.01368
800 MHz	0.05699
900 MHz	0.04746
1400 MHz	0.00048
1800 MHz	0.00567
1900 MHz	0.00022
2100 MHz	0.00574
2300 MHz	0.00220
2600 MHz TDD	0.00035
2600 MHz FDD	0.00011
3.4 GHz	0.00121
3.8 GHz	0.00291
Others	0.06030
Total	0.19732

Location 5

Measurement time:	12:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.06033
800 MHz	0.39911
900 MHz	0.10853
1400 MHz	0.00048
1800 MHz	0.01307
1900 MHz	0.00022
2100 MHz	0.01354
2300 MHz	0.01114
2600 MHz TDD	0.00036
2600 MHz FDD	0.00011
3.4 GHz	0.00123
3.8 GHz	0.00296
Others	0.06394
Total	0.67502

Location 6

Measurement time:	12:58
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.02576
800 MHz	0.09074
900 MHz	0.06610
1400 MHz	0.00050
1800 MHz	0.00190
1900 MHz	0.00023
2100 MHz	0.03915
2300 MHz	0.00856
2600 MHz TDD	0.00037
2600 MHz FDD	0.00011
3.4 GHz	0.00127
3.8 GHz	0.00303
Others	0.06249
Total	0.30021

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.