

### **ICNIRP Measurement Report**

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	05/12/23	Time Survey completed:	14:30
Survey address:	Blackburn BB2		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072599	24/01/2023
Probe	Agos Aria-6000 Antenna	60001024	30/03/2021
Cabling	1.7m Cable	1383	12/10/2023

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.


## Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

#### Notes

## **Survey locations**

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

<sup>\*\*</sup> All other frequencies between 420 MHz and 6 GHz.

# Location 1

Measurement time:	13:45
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0011
800 MHz	0.0008
900 MHz	0.0009
1400 MHz	0.0005
1800 MHz	0.0017
1900 MHz	0.0002
2100 MHz	0.0009
2300 MHz	0.0004
2600 MHz TDD	0.0003
2600 MHz FDD	0.0004
3.4 GHz	0.0022
3.8 GHz	0.0045
Others	0.1613
Total	0.1752

# Location 2

Measurement time:	13:52
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0012
800 MHz	0.0018
900 MHz	0.0012
1400 MHz	0.0006
1800 MHz	0.0010
1900 MHz	0.0002
2100 MHz	0.0012
2300 MHz	0.0004
2600 MHz TDD	0.0003
2600 MHz FDD	0.0004
3.4 GHz	0.0022
3.8 GHz	0.0047
Others	0.1689
Total	0.1840

# Location 3

Measurement time:	14:00
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0012
800 MHz	0.0021
900 MHz	0.0011
1400 MHz	0.0004
1800 MHz	0.0006
1900 MHz	0.0002
2100 MHz	0.0012
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0002
3.4 GHz	0.0022
3.8 GHz	0.0049
Others	0.1744
Total	0.1891

# Location 4

Measurement time:	14:08
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0012
800 MHz	0.0007
900 MHz	0.0007
1400 MHz	0.0005
1800 MHz	0.0006
1900 MHz	0.0002
2100 MHz	0.0006
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0002
3.4 GHz	0.0023
3.8 GHz	0.0050
Others	0.1792
Total	0.1920

Classification: CONFIDENTIAL

### Location 5

Measurement time:	14:16
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0012
800 MHz	0.0009
900 MHz	0.0008
1400 MHz	0.0005
1800 MHz	0.0007
1900 MHz	0.0002
2100 MHz	0.0007
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0002
3.4 GHz	0.0024
3.8 GHz	0.0052
Others	0.1828
Total	0.1961

### Location 6

Measurement time:	14:24
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0013
800 MHz	0.0009
900 MHz	0.0009
1400 MHz	0.0005
1800 MHz	0.0008
1900 MHz	0.0002
2100 MHz	0.0007
2300 MHz	0.0004
2600 MHz TDD	0.0004
2600 MHz FDD	0.0003
3.4 GHz	0.0025
3.8 GHz	0.0053
Others	0.1870
Total	0.2012

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.