

## ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

<b>Date of Survey:</b>	09/03/23	<b>Time Survey completed:</b>	11:37
<b>Survey address:</b>	Newtownabbey BT37		

Measurement equipment		Serial number	Calibration Date
<b>Meter</b>	Keysight Fieldfox N9950A Spectrum Analyser	US55240264	05/09/2022
<b>Probe</b>	Agos Aria-6000 Antenna	60001112	28/11/2022
<b>Cabling</b>	1.7m Cable	1314	28/11/2022

<sup>1</sup> <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

<sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

## Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

### Notes

\* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

\*\* All other frequencies between 420 MHz and 6 GHz.

### Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

**Location 1**

<b>Measurement time:</b>	10:50
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0078
800 MHz	0.0108
900 MHz	0.0197
1400 MHz	0.0002
1800 MHz	0.0002
1900 MHz	0.0001
2100 MHz	0.0011
2300 MHz	0.0002
2600 MHz TDD	0.0004
2600 MHz FDD	0.0001
3.4 GHz	0.0007
3.8 GHz	0.0017
Others	0.0286
<b>Total</b>	0.0716

**Location 2**

<b>Measurement time:</b>	10:58
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0079
800 MHz	0.0183
900 MHz	0.0306
1400 MHz	0.0002
1800 MHz	0.0002
1900 MHz	0.0001
2100 MHz	0.0079
2300 MHz	0.0002
2600 MHz TDD	0.0007
2600 MHz FDD	0.0001
3.4 GHz	0.0008
3.8 GHz	0.0018
Others	0.0303
<b>Total</b>	0.0990

**Location 3**

<b>Measurement time:</b>	11:06
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0092
800 MHz	0.0105
900 MHz	0.0239
1400 MHz	0.0002
1800 MHz	0.0002
1900 MHz	0.0001
2100 MHz	0.0015
2300 MHz	0.0002
2600 MHz TDD	0.0003
2600 MHz FDD	0.0001
3.4 GHz	0.0008
3.8 GHz	0.0019
Others	0.0317
<b>Total</b>	0.0806

**Location 4**

<b>Measurement time:</b>	11:15
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0053
800 MHz	0.0036
900 MHz	0.0079
1400 MHz	0.0002
1800 MHz	0.0003
1900 MHz	0.0001
2100 MHz	0.0007
2300 MHz	0.0002
2600 MHz TDD	0.0003
2600 MHz FDD	0.0001
3.4 GHz	0.0009
3.8 GHz	0.0020
Others	0.0330
<b>Total</b>	0.0546

**Location 5**

<b>Measurement time:</b>	11:22
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0037
800 MHz	0.0043
900 MHz	0.0143
1400 MHz	0.0002
1800 MHz	0.0003
1900 MHz	0.0001
2100 MHz	0.0008
2300 MHz	0.0002
2600 MHz TDD	0.0003
2600 MHz FDD	0.0001
3.4 GHz	0.0009
3.8 GHz	0.0020
Others	0.0346
<b>Total</b>	0.0618

**Location 6**

<b>Measurement time:</b>	11:31
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
700 MHz	0.0078
800 MHz	0.0159
900 MHz	0.0168
1400 MHz	0.0002
1800 MHz	0.0003
1900 MHz	0.0001
2100 MHz	0.0012
2300 MHz	0.0002
2600 MHz TDD	0.0005
2600 MHz FDD	0.0001
3.4 GHz	0.0009
3.8 GHz	0.0021
Others	0.0350
<b>Total</b>	0.0812

*Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.*