

### **ICNIRP Measurement Report**

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 420 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	21/09/23	Time Survey completed:	10:36
Survey address:	Saffron Walden CB1	1	

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY59221931	05/04/2023
Probe	Agos Aria-6000 Antenna	60001022	22/01/2021
Cabling	1.7m Cable	1187	04/01/2021

<sup>&</sup>lt;sup>1</sup> https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

<sup>&</sup>lt;sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

### Mobile bands covered by this report

Frequency Band	Frequency	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

#### Notes

### **Survey locations**

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Map data: © Google

<sup>\*</sup> This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations.

<sup>\*\*</sup> All other frequencies between 420 MHz and 6 GHz.

# Location 1

Measurement time:	09:53
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0064
800 MHz	0.0375
900 MHz	0.0202
1400 MHz	0.0020
1800 MHz	0.0092
1900 MHz	-
2100 MHz	0.0064
2300 MHz	-
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0005
3.8 GHz	0.0000
Others	0.0017
Total	0.0839

# Location 2

Measurement time:	10:01
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0065
800 MHz	0.0303
900 MHz	0.0705
1400 MHz	0.0037
1800 MHz	0.0121
1900 MHz	-
2100 MHz	0.0239
2300 MHz	-
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0006
3.8 GHz	0.0001
Others	0.0038
Total	0.1516

# Location 3

Measurement time:	10:08
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0305
800 MHz	0.0802
900 MHz	0.1702
1400 MHz	0.0062
1800 MHz	0.0058
1900 MHz	-
2100 MHz	0.0169
2300 MHz	-
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0007
3.8 GHz	0.0004
Others	0.0086
Total	0.3196

# Location 4

Measurement time:	10:16
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0133
800 MHz	0.0271
900 MHz	0.0395
1400 MHz	0.0021
1800 MHz	0.0107
1900 MHz	0.0000
2100 MHz	0.0106
2300 MHz	0.0001
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0014
3.8 GHz	0.0005
Others	0.0037
Total	0.1090

Classification: CONFIDENTIAL

#### Location 5

Measurement time:	10:22
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0379
800 MHz	0.1740
900 MHz	0.1885
1400 MHz	0.0013
1800 MHz	0.0084
1900 MHz	0.0000
2100 MHz	0.0188
2300 MHz	0.0001
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0008
3.8 GHz	0.0006
Others	0.0093
Total	0.4397

#### Location 6

Measurement time:	10:29
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
700 MHz	0.0080
800 MHz	0.0228
900 MHz	0.0180
1400 MHz	0.0021
1800 MHz	0.0093
1900 MHz	0.0000
2100 MHz	0.0051
2300 MHz	0.0001
2600 MHz TDD	0.0001
2600 MHz FDD	0.0001
3.4 GHz	0.0008
3.8 GHz	0.0008
Others	0.0036
Total	0.0708

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.