

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	10/12/2025	Time Survey completed:	13:45
Survey address:	London HP11		

	Measurement equipment	Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY58311497	28/08/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1023	08/07/2025
Cabling	1.7m cable	1407	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	13:07
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00837
174-230 MHz	0.00966
470-694 MHz	0.00756
700 MHz	0.00176
800 MHz	0.00518
900 MHz	0.00053
1400 MHz	0.00524
1800 MHz	0.00595
1900 MHz	0.00018
2100 MHz	0.00174
2300 MHz	0.00043
2600 MHz TDD	0.00034
2600 MHz FDD	0.00299
3.4 GHz	0.00255
3.8 GHz	0.00483
Others	0.13176
Total	0.18908

Location 2

Measurement time:	13:15
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00814
174-230 MHz	0.00932
470-694 MHz	0.00729
700 MHz	0.00119
800 MHz	0.00257
900 MHz	0.00052
1400 MHz	0.00236
1800 MHz	0.00544
1900 MHz	0.00017
2100 MHz	0.00223
2300 MHz	0.00043
2600 MHz TDD	0.00032
2600 MHz FDD	0.00036
3.4 GHz	0.00243
3.8 GHz	0.00464
Others	0.12644
Total	0.17384

Location 3

Measurement time:	13:22
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00773
174-230 MHz	0.00893
470-694 MHz	0.00702
700 MHz	0.00160
800 MHz	0.00502
900 MHz	0.00050
1400 MHz	0.00434
1800 MHz	0.01653
1900 MHz	0.00017
2100 MHz	0.00378
2300 MHz	0.00040
2600 MHz TDD	0.00031
2600 MHz FDD	0.00030
3.4 GHz	0.00294
3.8 GHz	0.00453
Others	0.12068
Total	0.18479

Location 4

Measurement time:	13:30
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00744
174-230 MHz	0.00861
470-694 MHz	0.00682
700 MHz	0.00113
800 MHz	0.00252
900 MHz	0.00049
1400 MHz	0.00253
1800 MHz	0.01528
1900 MHz	0.00016
2100 MHz	0.00439
2300 MHz	0.00042
2600 MHz TDD	0.00030
2600 MHz FDD	0.00138
3.4 GHz	0.00318
3.8 GHz	0.00422
Others	0.11643
Total	0.17531

Location 5

Measurement time:	13:39
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00731
174-230 MHz	0.00843
470-694 MHz	0.00670
700 MHz	0.00139
800 MHz	0.00415
900 MHz	0.00048
1400 MHz	0.00534
1800 MHz	0.00536
1900 MHz	0.00016
2100 MHz	0.00213
2300 MHz	0.00036
2600 MHz TDD	0.00029
2600 MHz FDD	0.00290
3.4 GHz	0.00212
3.8 GHz	0.00408
Others	0.11439
Total	0.16560

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.