

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	30/12/2025	Time Survey completed:	10:57
Survey address:	Sawston CB22		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072607	29/10/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1111	08/07/2025
Cabling	1.7m cable	1407	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at four locations and are presented in the following pages of this report.



Location 1

Measurement time:	10:21
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00884
174-230 MHz	0.00998
470-694 MHz	0.00805
700 MHz	0.00429
800 MHz	0.00850
900 MHz	0.00057
1400 MHz	0.00039
1800 MHz	0.00178
1900 MHz	0.00019
2100 MHz	0.00058
2300 MHz	0.00038
2600 MHz TDD	0.00035
2600 MHz FDD	0.00017
3.4 GHz	0.00182
3.8 GHz	0.00416
Others	0.12874
Total	0.17879

Location 2

Measurement time:	10:29
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00909
174-230 MHz	0.01020
470-694 MHz	0.00823
700 MHz	0.00189
800 MHz	0.00281
900 MHz	0.00075
1400 MHz	0.00041
1800 MHz	0.00208
1900 MHz	0.00019
2100 MHz	0.00084
2300 MHz	0.00039
2600 MHz TDD	0.00035
2600 MHz FDD	0.00017
3.4 GHz	0.00187
3.8 GHz	0.00429
Others	0.13195
Total	0.17551

Location 3

Measurement time:	10:41
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00919
174-230 MHz	0.01040
470-694 MHz	0.00840
700 MHz	0.00403
800 MHz	0.01135
900 MHz	0.00060
1400 MHz	0.00041
1800 MHz	0.00467
1900 MHz	0.00020
2100 MHz	0.00077
2300 MHz	0.00040
2600 MHz TDD	0.00036
2600 MHz FDD	0.00017
3.4 GHz	0.00192
3.8 GHz	0.00438
Others	0.13508
Total	0.19233

Location 4

Measurement time:	10:51
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00924
174-230 MHz	0.01044
470-694 MHz	0.00840
700 MHz	0.00427
800 MHz	0.01033
900 MHz	0.00060
1400 MHz	0.00041
1800 MHz	0.00126
1900 MHz	0.00020
2100 MHz	0.00063
2300 MHz	0.00040
2600 MHz TDD	0.00037
2600 MHz FDD	0.00018
3.4 GHz	0.00194
3.8 GHz	0.00443
Others	0.13631
Total	0.18939

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.