

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	25/11/2025	Time Survey completed:	13:35
Survey address:	London N21		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY58311497	28/08/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1023	08/07/2025
Cabling	1.7m cable	1407	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	12:47
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00624
174-230 MHz	0.00703
470-694 MHz	0.00573
700 MHz	0.00312
800 MHz	0.00615
900 MHz	0.01994
1400 MHz	0.00828
1800 MHz	0.00477
1900 MHz	0.00013
2100 MHz	0.00693
2300 MHz	0.00190
2600 MHz TDD	0.00029
2600 MHz FDD	0.00140
3.4 GHz	0.00207
3.8 GHz	0.00438
Others	0.09512
Total	0.17349

Location 2

Measurement time:	12:56
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00629
174-230 MHz	0.00721
470-694 MHz	0.00578
700 MHz	0.00589
800 MHz	0.00682
900 MHz	0.02266
1400 MHz	0.00682
1800 MHz	0.00298
1900 MHz	0.00013
2100 MHz	0.00584
2300 MHz	0.00157
2600 MHz TDD	0.00027
2600 MHz FDD	0.00090
3.4 GHz	0.00316
3.8 GHz	0.00641
Others	0.09631
Total	0.17904

Location 3

Measurement time:	13:08
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00650
174-230 MHz	0.00738
470-694 MHz	0.00597
700 MHz	0.00161
800 MHz	0.00508
900 MHz	0.03644
1400 MHz	0.00464
1800 MHz	0.01154
1900 MHz	0.00014
2100 MHz	0.00925
2300 MHz	0.00145
2600 MHz TDD	0.00029
2600 MHz FDD	0.00126
3.4 GHz	0.00380
3.8 GHz	0.00402
Others	0.10020
Total	0.19957

Location 4

Measurement time:	13:18
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00650
174-230 MHz	0.00744
470-694 MHz	0.00601
700 MHz	0.00079
800 MHz	0.00043
900 MHz	0.00046
1400 MHz	0.00031
1800 MHz	0.00047
1900 MHz	0.00014
2100 MHz	0.00042
2300 MHz	0.00032
2600 MHz TDD	0.00026
2600 MHz FDD	0.00013
3.4 GHz	0.00141
3.8 GHz	0.00346
Others	0.09993
Total	0.12847

Location 5

Measurement time:	13:29
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00651
174-230 MHz	0.00744
470-694 MHz	0.00601
700 MHz	0.00228
800 MHz	0.00465
900 MHz	0.02377
1400 MHz	0.00826
1800 MHz	0.00349
1900 MHz	0.00014
2100 MHz	0.00602
2300 MHz	0.00195
2600 MHz TDD	0.00029
2600 MHz FDD	0.00117
3.4 GHz	0.00218
3.8 GHz	0.00519
Others	0.10089
Total	0.18024

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.