

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	28/10/2025	Time Survey completed:	11:12
Survey address:	Hertford SG14		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY59221931	13/08/2025
Probe	Agos Aria-6000 Antenna	1111	08/07/2025
Cabling	1.7m cable	1313	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Location 1

Measurement time:	10:26
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00245
174-230 MHz	0.00198
470-694 MHz	0.00187
700 MHz	0.00025
800 MHz	0.00267
900 MHz	0.00301
1400 MHz	0.00009
1800 MHz	0.00075
1900 MHz	0.00005
2100 MHz	0.00050
2300 MHz	0.00009
2600 MHz TDD	0.00009
2600 MHz FDD	0.00007
3.4 GHz	0.00058
3.8 GHz	0.00118
Others	0.03289
Total	0.04849

Location 2

Measurement time:	10:34
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00241
174-230 MHz	0.00195
470-694 MHz	0.00188
700 MHz	0.00025
800 MHz	0.00433
900 MHz	0.00247
1400 MHz	0.00009
1800 MHz	0.00081
1900 MHz	0.00004
2100 MHz	0.00074
2300 MHz	0.00009
2600 MHz TDD	0.00008
2600 MHz FDD	0.00006
3.4 GHz	0.00057
3.8 GHz	0.00117
Others	0.03238
Total	0.04932

Location 3

Measurement time:	10:41
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00241
174-230 MHz	0.00197
470-694 MHz	0.00196
700 MHz	0.00028
800 MHz	0.00654
900 MHz	0.03058
1400 MHz	0.00009
1800 MHz	0.00327
1900 MHz	0.00004
2100 MHz	0.00151
2300 MHz	0.00009
2600 MHz TDD	0.00008
2600 MHz FDD	0.00007
3.4 GHz	0.00058
3.8 GHz	0.00116
Others	0.03407
Total	0.08471

Location 4

Measurement time:	10:48
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00238
174-230 MHz	0.00195
470-694 MHz	0.00183
700 MHz	0.00025
800 MHz	0.00919
900 MHz	0.00646
1400 MHz	0.00009
1800 MHz	0.00717
1900 MHz	0.00004
2100 MHz	0.00169
2300 MHz	0.00009
2600 MHz TDD	0.00008
2600 MHz FDD	0.00007
3.4 GHz	0.00058
3.8 GHz	0.00117
Others	0.03253
Total	0.06557

Location 5

Measurement time:	10:56
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00239
174-230 MHz	0.00196
470-694 MHz	0.00245
700 MHz	0.00026
800 MHz	0.01319
900 MHz	0.01323
1400 MHz	0.00010
1800 MHz	0.00317
1900 MHz	0.00004
2100 MHz	0.00289
2300 MHz	0.00009
2600 MHz TDD	0.00009
2600 MHz FDD	0.00007
3.4 GHz	0.00062
3.8 GHz	0.00117
Others	0.03318
Total	0.07489

Location 6

Measurement time:	11:06
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00241
174-230 MHz	0.00197
470-694 MHz	0.00185
700 MHz	0.00024
800 MHz	0.00350
900 MHz	0.00154
1400 MHz	0.00008
1800 MHz	0.00087
1900 MHz	0.00004
2100 MHz	0.00046
2300 MHz	0.00009
2600 MHz TDD	0.00009
2600 MHz FDD	0.00007
3.4 GHz	0.00058
3.8 GHz	0.00117
Others	0.03255
Total	0.04751

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.