

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	20/04/2026	Time Survey completed:	15:19
Survey address:	Long Sutton PE12		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072591	11/12/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1023	08/07/2025
Cabling	1.7m cable	1188	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	14:12
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01416
174-230 MHz	0.01590
470-694 MHz	0.01254
700 MHz	0.00171
800 MHz	0.00211
900 MHz	0.00115
1400 MHz	0.00065
1800 MHz	0.00209
1900 MHz	0.00031
2100 MHz	0.00108
2300 MHz	0.00063
2600 MHz TDD	0.00054
2600 MHz FDD	0.00023
3.4 GHz	0.00253
3.8 GHz	0.00594
Others	0.20006
Total	0.26165

Location 2

Measurement time:	14:30
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01522
174-230 MHz	0.01711
470-694 MHz	0.01337
700 MHz	0.00185
800 MHz	0.00250
900 MHz	0.00101
1400 MHz	0.00070
1800 MHz	0.00233
1900 MHz	0.00034
2100 MHz	0.00105
2300 MHz	0.00069
2600 MHz TDD	0.00059
2600 MHz FDD	0.00025
3.4 GHz	0.00280
3.8 GHz	0.00652
Others	0.21739
Total	0.28371

Location 3

Measurement time:	14:43
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01529
174-230 MHz	0.01731
470-694 MHz	0.01358
700 MHz	0.00185
800 MHz	0.00248
900 MHz	0.00401
1400 MHz	0.00071
1800 MHz	0.00198
1900 MHz	0.00034
2100 MHz	0.00113
2300 MHz	0.00070
2600 MHz TDD	0.00059
2600 MHz FDD	0.00025
3.4 GHz	0.00283
3.8 GHz	0.00661
Others	0.21976
Total	0.28944

Location 4

Measurement time:	15:00
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01641
174-230 MHz	0.01827
470-694 MHz	0.01420
700 MHz	0.00196
800 MHz	0.00347
900 MHz	0.00111
1400 MHz	0.00075
1800 MHz	0.00441
1900 MHz	0.00036
2100 MHz	0.00119
2300 MHz	0.00073
2600 MHz TDD	0.00063
2600 MHz FDD	0.00027
3.4 GHz	0.00300
3.8 GHz	0.00700
Others	0.23244
Total	0.30619

Location 5

Measurement time:	15:13
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01664
174-230 MHz	0.01864
470-694 MHz	0.01448
700 MHz	0.00197
800 MHz	0.00177
900 MHz	0.00124
1400 MHz	0.00076
1800 MHz	0.00236
1900 MHz	0.00037
2100 MHz	0.00117
2300 MHz	0.00075
2600 MHz TDD	0.00064
2600 MHz FDD	0.00028
3.4 GHz	0.00308
3.8 GHz	0.00713
Others	0.23652
Total	0.30780

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.