

# ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)<sup>1</sup>, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor<sup>2</sup> of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

<b>Date of Survey:</b>	03/02/2026	<b>Time Survey completed:</b>	15:24
<b>Survey address:</b>	Birmingham B36		

Measurement equipment		Serial number	Calibration Date
<b>Meter</b>	Keysight Fieldfox N9915A Spectrum Analyser	MY59221930	03/06/2025
<b>Probe</b>	Agos Aria-6000 Antenna	ARIA6000-1158	08/07/2025
<b>Cabling</b>	1.7m cable	1458	08/07/2025

---

<sup>1</sup> <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

<sup>2</sup> The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

## Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

## Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

\* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. \*\* All other frequencies between 30 MHz and 6 GHz.

## Survey locations

---

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



**Location 1**

<b>Measurement time:</b>	<b>14:24</b>
<b>Frequency band</b>	<b>Percentage of the ICNIRP reference levels for general public exposure</b>
87.5-108 MHz	0.00571
174-230 MHz	0.00170
470-694 MHz	0.00158
700 MHz	0.00648
800 MHz	0.00697
900 MHz	0.01682
1400 MHz	0.00758
1800 MHz	0.01623
1900 MHz	0.00004
2100 MHz	0.00278
2300 MHz	0.00199
2600 MHz TDD	0.00007
2600 MHz FDD	0.00017
3.4 GHz	0.00088
3.8 GHz	0.00085
Others	0.02724
<b>Total</b>	<b>0.09709</b>

## Location 2

Measurement time:	14:35
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00364
174-230 MHz	0.00176
470-694 MHz	0.00162
700 MHz	0.00062
800 MHz	0.01052
900 MHz	0.00393
1400 MHz	0.00057
1800 MHz	0.00059
1900 MHz	0.00004
2100 MHz	0.00146
2300 MHz	0.00021
2600 MHz TDD	0.00008
2600 MHz FDD	0.00046
3.4 GHz	0.00080
3.8 GHz	0.00077
Others	0.02647
<b>Total</b>	<b>0.05356</b>

### Location 3

Measurement time:	14:48
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00461
174-230 MHz	0.00183
470-694 MHz	0.00169
700 MHz	0.00050
800 MHz	0.00350
900 MHz	0.00279
1400 MHz	0.00018
1800 MHz	0.00038
1900 MHz	0.00004
2100 MHz	0.00172
2300 MHz	0.00023
2600 MHz TDD	0.00013
2600 MHz FDD	0.00168
3.4 GHz	0.00061
3.8 GHz	0.00085
Others	0.02760
<b>Total</b>	<b>0.04835</b>

#### Location 4

Measurement time:	14:58
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00792
174-230 MHz	0.00192
470-694 MHz	0.00173
700 MHz	0.00119
800 MHz	0.00154
900 MHz	0.00079
1400 MHz	0.00206
1800 MHz	0.00362
1900 MHz	0.00004
2100 MHz	0.00178
2300 MHz	0.00039
2600 MHz TDD	0.00008
2600 MHz FDD	0.00187
3.4 GHz	0.00079
3.8 GHz	0.00109
Others	0.02833
<b>Total</b>	<b>0.05515</b>

#### Location 5

Measurement time:	15:08
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00403
174-230 MHz	0.00189
470-694 MHz	0.00173
700 MHz	0.01147
800 MHz	0.00522
900 MHz	0.01003
1400 MHz	0.00472
1800 MHz	0.01009
1900 MHz	0.00004
2100 MHz	0.00237
2300 MHz	0.00219
2600 MHz TDD	0.00009
2600 MHz FDD	0.00102
3.4 GHz	0.00084
3.8 GHz	0.00119
Others	0.02971
<b>Total</b>	<b>0.08663</b>

Location 6

Measurement time:	15:18
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00624
174-230 MHz	0.00190
470-694 MHz	0.00176
700 MHz	0.00411
800 MHz	0.00761
900 MHz	0.01170
1400 MHz	0.00482
1800 MHz	0.01420
1900 MHz	0.00004
2100 MHz	0.00284
2300 MHz	0.00077
2600 MHz TDD	0.00008
2600 MHz FDD	0.00019
3.4 GHz	0.00088
3.8 GHz	0.00110
Others	0.02995
<b>Total</b>	<b>0.08819</b>

*Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.*