

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	12/02/2026	Time Survey completed:	15:13
Survey address:	Poulton FY6		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY59221930	03/06/2025
Probe	Agos Aria-6000 Antenna	ARIA6000-1158	08/07/2025
Cabling	1.7m cable	1458	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

* This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	14:26
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00458
174-230 MHz	0.00204
470-694 MHz	0.00158
700 MHz	0.00120
800 MHz	0.00956
900 MHz	0.00374
1400 MHz	0.00012
1800 MHz	0.01815
1900 MHz	0.00004
2100 MHz	0.00090
2300 MHz	0.00064
2600 MHz TDD	0.00007
2600 MHz FDD	0.00007
3.4 GHz	0.00058
3.8 GHz	0.00091
Others	0.03865
Total	0.08282

Location 2

Measurement time:	14:35
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00933
174-230 MHz	0.00213
470-694 MHz	0.00172
700 MHz	0.00061
800 MHz	0.00181
900 MHz	0.00100
1400 MHz	0.00010
1800 MHz	0.00138
1900 MHz	0.00005
2100 MHz	0.00099
2300 MHz	0.00042
2600 MHz TDD	0.00008
2600 MHz FDD	0.00006
3.4 GHz	0.00049
3.8 GHz	0.00088
Others	0.04106
Total	0.06210

Location 3

Measurement time:	14:47
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00516
174-230 MHz	0.00228
470-694 MHz	0.00183
700 MHz	0.00205
800 MHz	0.02337
900 MHz	0.00855
1400 MHz	0.00008
1800 MHz	0.01576
1900 MHz	0.00005
2100 MHz	0.00260
2300 MHz	0.00117
2600 MHz TDD	0.00008
2600 MHz FDD	0.00364
3.4 GHz	0.00078
3.8 GHz	0.00134
Others	0.16590
Total	0.23465

Location 4

Measurement time:	14:56
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00497
174-230 MHz	0.00230
470-694 MHz	0.00182
700 MHz	0.00304
800 MHz	0.03152
900 MHz	0.01572
1400 MHz	0.00009
1800 MHz	0.01908
1900 MHz	0.00005
2100 MHz	0.00427
2300 MHz	0.00241
2600 MHz TDD	0.00008
2600 MHz FDD	0.00064
3.4 GHz	0.00084
3.8 GHz	0.00116
Others	0.11105
Total	0.19904

Location 5

Measurement time:	15:07
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00539
174-230 MHz	0.00237
470-694 MHz	0.00180
700 MHz	0.00310
800 MHz	0.00882
900 MHz	0.00253
1400 MHz	0.00013
1800 MHz	0.04266
1900 MHz	0.00005
2100 MHz	0.00101
2300 MHz	0.00071
2600 MHz TDD	0.00009
2600 MHz FDD	0.00008
3.4 GHz	0.00064
3.8 GHz	0.00117
Others	0.05261
Total	0.12315

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.