ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)[1], with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor[2] of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	06/07/2026	**Time Survey completed:**	14:56
Survey address:	Pinchbeck PE11		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072591	11/12/2025
Probe	Agos Aria-6000 Antenna	AGOS-6000-1023	08/07/2025
Cabling	1.7m cable	1188	02/02/2026

[1] https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

[2] The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	13:51
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01533
174-230 MHz	0.01709
470-694 MHz	0.01339
700 MHz	0.00238
800 MHz	0.00593
900 MHz	0.01992
1400 MHz	0.00070
1800 MHz	0.00097
1900 MHz	0.00034
2100 MHz	0.00134
2300 MHz	0.00068
2600 MHz TDD	0.00059
2600 MHz FDD	0.00025
3.4 GHz	0.00276
3.8 GHz	0.00643
Others	0.21638
Total	**0.30449**

Location 2

Measurement time:	14:02
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01685
174-230 MHz	0.01908
470-694 MHz	0.01481
700 MHz	0.00407
800 MHz	0.01249
900 MHz	0.01809
1400 MHz	0.00078
1800 MHz	0.00107
1900 MHz	0.00038
2100 MHz	0.00212
2300 MHz	0.00076
2600 MHz TDD	0.00065
2600 MHz FDD	0.00028
3.4 GHz	0.00315
3.8 GHz	0.00733
Others	0.24337
Total	**0.34528**

Location 3

Measurement time:	14:14
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01830
174-230 MHz	0.02057
470-694 MHz	0.01588
700 MHz	0.00560
800 MHz	0.05156
900 MHz	0.04204
1400 MHz	0.00084
1800 MHz	0.00116
1900 MHz	0.00040
2100 MHz	0.00336
2300 MHz	0.00082
2600 MHz TDD	0.00070
2600 MHz FDD	0.00031
3.4 GHz	0.00346
3.8 GHz	0.00805
Others	0.26449
Total	**0.43754**

Location 4

Measurement time:	14:31
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01992
174-230 MHz	0.02247
470-694 MHz	0.01711
700 MHz	0.00274
800 MHz	0.00395
900 MHz	0.00768
1400 MHz	0.00091
1800 MHz	0.00126
1900 MHz	0.00044
2100 MHz	0.00218
2300 MHz	0.00090
2600 MHz TDD	0.00077
2600 MHz FDD	0.00034
3.4 GHz	0.00384
3.8 GHz	0.00893
Others	0.28788
Total	**0.38133**

Location 5

Measurement time:	14:50
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.02109
174-230 MHz	0.02379
470-694 MHz	0.01806
700 MHz	0.00315
800 MHz	0.00691
900 MHz	0.01874
1400 MHz	0.00098
1800 MHz	0.00135
1900 MHz	0.00046
2100 MHz	0.00183
2300 MHz	0.00096
2600 MHz TDD	0.00083
2600 MHz FDD	0.00036
3.4 GHz	0.00411
3.8 GHz	0.00961
Others	0.30813
Total	**0.42039**

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.