ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)[1], with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor[2] of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	09/07/2026	**Time Survey completed:**	11:36
Survey address:	Pockley YO62		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY59221929	11/03/2026
Probe	Agos Aria-6000 Antenna	AGOS-6000-1156	08/07/2025
Cabling	1.7m cable	2063	18/02/2026

[1] https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

[2] The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Location 1

Measurement time:	10:44
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00248
174-230 MHz	0.00196
470-694 MHz	0.00339
700 MHz	0.00173
800 MHz	0.01624
900 MHz	0.02075
1400 MHz	0.00008
1800 MHz	0.00397
1900 MHz	0.00004
2100 MHz	0.00011
2300 MHz	0.00008
2600 MHz TDD	0.00008
2600 MHz FDD	0.00005
3.4 GHz	0.00047
3.8 GHz	0.00095
Others	0.03108
Total	**0.08348**

Location 2

Measurement time:	10:52
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00278
174-230 MHz	0.00450
470-694 MHz	0.01145
700 MHz	0.00178
800 MHz	0.01887
900 MHz	0.00396
1400 MHz	0.00009
1800 MHz	0.00096
1900 MHz	0.00005
2100 MHz	0.00012
2300 MHz	0.00009
2600 MHz TDD	0.00009
2600 MHz FDD	0.00006
3.4 GHz	0.00054
3.8 GHz	0.00108
Others	0.03361
Total	**0.08002**

Location 3

Measurement time:	11:02
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00293
174-230 MHz	0.00479
470-694 MHz	0.02065
700 MHz	0.00181
800 MHz	0.02947
900 MHz	0.00591
1400 MHz	0.00009
1800 MHz	0.00045
1900 MHz	0.00005
2100 MHz	0.00013
2300 MHz	0.00010
2600 MHz TDD	0.00009
2600 MHz FDD	0.00007
3.4 GHz	0.00059
3.8 GHz	0.00118
Others	0.03613
Total	**0.10444**

Location 4

Measurement time:	11:14
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00293
174-230 MHz	0.00324
470-694 MHz	0.00658
700 MHz	0.00171
800 MHz	0.03997
900 MHz	0.02110
1400 MHz	0.00010
1800 MHz	0.00037
1900 MHz	0.00005
2100 MHz	0.00014
2300 MHz	0.00010
2600 MHz TDD	0.00010
2600 MHz FDD	0.00007
3.4 GHz	0.00061
3.8 GHz	0.00123
Others	0.03772
Total	**0.11603**

Location 5

Measurement time:	11:22
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00337
174-230 MHz	0.00269
470-694 MHz	0.00421
700 MHz	0.00137
800 MHz	0.02258
900 MHz	0.02051
1400 MHz	0.00010
1800 MHz	0.00040
1900 MHz	0.00005
2100 MHz	0.00014
2300 MHz	0.00010
2600 MHz TDD	0.00010
2600 MHz FDD	0.00007
3.4 GHz	0.00063
3.8 GHz	0.00127
Others	0.03886
Total	**0.09646**

Location 6

Measurement time:	11:30
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.00307
174-230 MHz	0.00272
470-694 MHz	0.00479
700 MHz	0.00202
800 MHz	0.02050
900 MHz	0.02525
1400 MHz	0.00010
1800 MHz	0.00218
1900 MHz	0.00005
2100 MHz	0.00014
2300 MHz	0.00010
2600 MHz TDD	0.00010
2600 MHz FDD	0.00007
3.4 GHz	0.00064
3.8 GHz	0.00129
Others	0.04002
Total	**0.10306**

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.