ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)[1], with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor[2] of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	18/06/2026	**Time Survey completed:**	13:53
Survey address:	Boston PE21		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072591	11/12/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1023	08/07/2025
Cabling	1.7m cable	1188	02/02/2026

[1] https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

[2] The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	12:20
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01436
174-230 MHz	0.01606
470-694 MHz	0.01268
700 MHz	0.02651
800 MHz	0.09070
900 MHz	0.06155
1400 MHz	0.00070
1800 MHz	0.00393
1900 MHz	0.00032
2100 MHz	0.00489
2300 MHz	0.00133
2600 MHz TDD	0.00055
2600 MHz FDD	0.00211
3.4 GHz	0.00258
3.8 GHz	0.00599
Others	0.20608
Total	**0.45034**

Location 2

Measurement time:	12:40
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01712
174-230 MHz	0.01910
470-694 MHz	0.01479
700 MHz	0.02417
800 MHz	0.01824
900 MHz	0.01739
1400 MHz	0.00082
1800 MHz	0.01086
1900 MHz	0.00038
2100 MHz	0.01321
2300 MHz	0.00144
2600 MHz TDD	0.00065
2600 MHz FDD	0.00136
3.4 GHz	0.00318
3.8 GHz	0.00735
Others	0.24397
Total	**0.39402**

Location 3

Measurement time:	13:16
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.02007
174-230 MHz	0.02248
470-694 MHz	0.01717
700 MHz	0.01424
800 MHz	0.01777
900 MHz	0.00836
1400 MHz	0.00096
1800 MHz	0.01369
1900 MHz	0.00044
2100 MHz	0.00880
2300 MHz	0.00171
2600 MHz TDD	0.00077
2600 MHz FDD	0.00146
3.4 GHz	0.00386
3.8 GHz	0.00890
Others	0.28859
Total	**0.42928**

Location 4

Measurement time:	13:35
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.02012
174-230 MHz	0.02271
470-694 MHz	0.01737
700 MHz	0.01113
800 MHz	0.01934
900 MHz	0.00823
1400 MHz	0.00100
1800 MHz	0.00806
1900 MHz	0.00044
2100 MHz	0.00704
2300 MHz	0.00182
2600 MHz TDD	0.00079
2600 MHz FDD	0.00082
3.4 GHz	0.00395
3.8 GHz	0.00908
Others	0.30136
Total	**0.43326**

Location 5

Measurement time:	13:47
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.02007
174-230 MHz	0.02265
470-694 MHz	0.01726
700 MHz	0.02648
800 MHz	0.06250
900 MHz	0.04904
1400 MHz	0.00104
1800 MHz	0.00490
1900 MHz	0.00044
2100 MHz	0.00575
2300 MHz	0.00129
2600 MHz TDD	0.00078
2600 MHz FDD	0.00168
3.4 GHz	0.00385
3.8 GHz	0.00896
Others	0.29200
Total	**0.51869**

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.