

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	25/06/2026	Time Survey completed:	09:02
Survey address:	Liss GU33		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072613	07/07/2025
Probe	Agos Aria-6000 Antenna	AGOS-6000-1157	08/07/2025
Cabling	1.7m cable	2064	15/11/2024

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	08:15
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01010
174-230 MHz	0.01145
470-694 MHz	0.00861
700 MHz	0.00115
800 MHz	0.00062
900 MHz	0.00061
1400 MHz	0.00042
1800 MHz	0.00058
1900 MHz	0.00020
2100 MHz	0.00053
2300 MHz	0.00042
2600 MHz TDD	0.00038
2600 MHz FDD	0.00022
3.4 GHz	0.00245
3.8 GHz	0.00591
Others	0.16009
Total	0.20372

Location 2

Measurement time:	08:24
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01126
174-230 MHz	0.01261
470-694 MHz	0.00937
700 MHz	0.00124
800 MHz	0.00089
900 MHz	0.00135
1400 MHz	0.00046
1800 MHz	0.00064
1900 MHz	0.00022
2100 MHz	0.00058
2300 MHz	0.00046
2600 MHz TDD	0.00042
2600 MHz FDD	0.00025
3.4 GHz	0.00275
3.8 GHz	0.00664
Others	0.17754
Total	0.22668

Location 3

Measurement time:	08:34
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01212
174-230 MHz	0.01357
470-694 MHz	0.01006
700 MHz	0.00133
800 MHz	0.00210
900 MHz	0.00113
1400 MHz	0.00050
1800 MHz	0.00069
1900 MHz	0.00024
2100 MHz	0.00063
2300 MHz	0.00050
2600 MHz TDD	0.00045
2600 MHz FDD	0.00027
3.4 GHz	0.00302
3.8 GHz	0.00730
Others	0.19339
Total	0.24729

Location 4

Measurement time:	08:45
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01302
174-230 MHz	0.01461
470-694 MHz	0.01078
700 MHz	0.00142
800 MHz	0.00081
900 MHz	0.00076
1400 MHz	0.00053
1800 MHz	0.00074
1900 MHz	0.00025
2100 MHz	0.00068
2300 MHz	0.00054
2600 MHz TDD	0.00049
2600 MHz FDD	0.00030
3.4 GHz	0.00330
3.8 GHz	0.00796
Others	0.20923
Total	0.26543

Location 5

Measurement time:	08:56
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01374
174-230 MHz	0.01539
470-694 MHz	0.01131
700 MHz	0.00149
800 MHz	0.00089
900 MHz	0.00080
1400 MHz	0.00056
1800 MHz	0.00078
1900 MHz	0.00027
2100 MHz	0.00072
2300 MHz	0.00057
2600 MHz TDD	0.00052
2600 MHz FDD	0.00031
3.4 GHz	0.00351
3.8 GHz	0.00847
Others	0.22133
Total	0.28067

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.