

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	23/06/2026	Time Survey completed:	09:57
Survey address:	Walton Summit PR5		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	US55240265	31/10/2025
Probe	Agos Aria-6000 Antenna	AGOS-6000-1022	08/07/2025
Cabling	1.7m cable	1405	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	08:50
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01378
174-230 MHz	0.00746
470-694 MHz	0.00566
700 MHz	0.02379
800 MHz	0.15963
900 MHz	0.08070
1400 MHz	0.00647
1800 MHz	0.00371
1900 MHz	0.00010
2100 MHz	0.01003
2300 MHz	0.00097
2600 MHz TDD	0.00173
2600 MHz FDD	0.00201
3.4 GHz	0.00183
3.8 GHz	0.00225
Others	0.29136
Total	0.61145

Location 2

Measurement time:	08:59
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00869
174-230 MHz	0.00785
470-694 MHz	0.00604
700 MHz	0.01023
800 MHz	0.03243
900 MHz	0.04665
1400 MHz	0.00763
1800 MHz	0.00249
1900 MHz	0.00011
2100 MHz	0.00800
2300 MHz	0.00109
2600 MHz TDD	0.00072
2600 MHz FDD	0.00063
3.4 GHz	0.00151
3.8 GHz	0.00242
Others	0.10481
Total	0.24130

Location 3

Measurement time:	09:34
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01082
174-230 MHz	0.00962
470-694 MHz	0.00737
700 MHz	0.00684
800 MHz	0.01562
900 MHz	0.03712
1400 MHz	0.01047
1800 MHz	0.00303
1900 MHz	0.00013
2100 MHz	0.00600
2300 MHz	0.00053
2600 MHz TDD	0.00060
2600 MHz FDD	0.00057
3.4 GHz	0.00167
3.8 GHz	0.00317
Others	0.13028
Total	0.24386

Location 4

Measurement time:	09:44
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01097
174-230 MHz	0.01006
470-694 MHz	0.00776
700 MHz	0.01795
800 MHz	0.04390
900 MHz	0.03980
1400 MHz	0.00869
1800 MHz	0.00416
1900 MHz	0.00014
2100 MHz	0.02194
2300 MHz	0.00193
2600 MHz TDD	0.00231
2600 MHz FDD	0.00105
3.4 GHz	0.00177
3.8 GHz	0.00344
Others	0.13623
Total	0.31212

Location 5

Measurement time:	09:51
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01132
174-230 MHz	0.01052
470-694 MHz	0.00809
700 MHz	0.01372
800 MHz	0.07685
900 MHz	0.03870
1400 MHz	0.01008
1800 MHz	0.00545
1900 MHz	0.00015
2100 MHz	0.01242
2300 MHz	0.00153
2600 MHz TDD	0.00185
2600 MHz FDD	0.00165
3.4 GHz	0.00330
3.8 GHz	0.00369
Others	0.14070
Total	0.34002

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.