

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	25/03/2026	Time Survey completed:	13:32
Survey address:	Barton Le Clay MK45		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072614	21/07/2025
Probe	Agos Aria-6000 Antenna	1023	08/07/2025
Cabling	1.7m cable	1188	02/02/2026

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at four locations and are presented in the following pages of this report.



Location 1

Measurement time:	12:41
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00205
174-230 MHz	0.00167
470-694 MHz	0.00155
700 MHz	0.00099
800 MHz	0.01855
900 MHz	0.02192
1400 MHz	0.00007
1800 MHz	0.01283
1900 MHz	0.00004
2100 MHz	0.00072
2300 MHz	0.00310
2600 MHz TDD	0.00007
2600 MHz FDD	0.00006
3.4 GHz	0.00047
3.8 GHz	0.00159
Others	0.02790
Total	0.09358

Location 2

Measurement time:	13:10
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00207
174-230 MHz	0.00169
470-694 MHz	0.00159
700 MHz	0.00071
800 MHz	0.00772
900 MHz	0.01059
1400 MHz	0.00007
1800 MHz	0.01012
1900 MHz	0.00004
2100 MHz	0.00066
2300 MHz	0.00126
2600 MHz TDD	0.00007
2600 MHz FDD	0.00008
3.4 GHz	0.00047
3.8 GHz	0.00113
Others	0.02797
Total	0.06624

Location 3

Measurement time:	13:18
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00211
174-230 MHz	0.00173
470-694 MHz	0.00162
700 MHz	0.00082
800 MHz	0.00791
900 MHz	0.04851
1400 MHz	0.00007
1800 MHz	0.01668
1900 MHz	0.00004
2100 MHz	0.00150
2300 MHz	0.00097
2600 MHz TDD	0.00007
2600 MHz FDD	0.00008
3.4 GHz	0.00049
3.8 GHz	0.00122
Others	0.02948
Total	0.11329

Location 4

Measurement time:	13:26
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00217
174-230 MHz	0.00176
470-694 MHz	0.00163
700 MHz	0.00086
800 MHz	0.02152
900 MHz	0.01674
1400 MHz	0.00007
1800 MHz	0.01616
1900 MHz	0.00004
2100 MHz	0.00049
2300 MHz	0.00165
2600 MHz TDD	0.00008
2600 MHz FDD	0.00008
3.4 GHz	0.00050
3.8 GHz	0.00133
Others	0.02951
Total	0.09459

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.