

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	31/03/2026	Time Survey completed:	11:33
Survey address:	London HA7		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072597	15/08/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1157	08/07/2025
Cabling	1.7m cable	1379	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at four locations and are presented in the following pages of this report.



Location 1

Measurement time:	11:01
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01054
174-230 MHz	0.01080
470-694 MHz	0.00845
700 MHz	0.01830
800 MHz	0.01612
900 MHz	0.04301
1400 MHz	0.00476
1800 MHz	0.00208
1900 MHz	0.00021
2100 MHz	0.00928
2300 MHz	0.00276
2600 MHz TDD	0.00037
2600 MHz FDD	0.00017
3.4 GHz	0.00360
3.8 GHz	0.00426
Others	0.15662
Total	0.29132

Location 2

Measurement time:	11:09
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00997
174-230 MHz	0.01145
470-694 MHz	0.00898
700 MHz	0.01657
800 MHz	0.01193
900 MHz	0.02603
1400 MHz	0.00263
1800 MHz	0.00220
1900 MHz	0.00022
2100 MHz	0.01443
2300 MHz	0.00179
2600 MHz TDD	0.00041
2600 MHz FDD	0.00019
3.4 GHz	0.00292
3.8 GHz	0.00461
Others	0.15024
Total	0.26460

Location 3

Measurement time:	11:18
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01092
174-230 MHz	0.01178
470-694 MHz	0.00925
700 MHz	0.01210
800 MHz	0.00423
900 MHz	0.00082
1400 MHz	0.00934
1800 MHz	0.00230
1900 MHz	0.00023
2100 MHz	0.00346
2300 MHz	0.00048
2600 MHz TDD	0.00041
2600 MHz FDD	0.00018
3.4 GHz	0.00397
3.8 GHz	0.00472
Others	0.17472
Total	0.24891

Location 4

Measurement time:	11:27
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.01118
174-230 MHz	0.01191
470-694 MHz	0.00922
700 MHz	0.02152
800 MHz	0.01577
900 MHz	0.03897
1400 MHz	0.00328
1800 MHz	0.00260
1900 MHz	0.00023
2100 MHz	0.01493
2300 MHz	0.00284
2600 MHz TDD	0.00041
2600 MHz FDD	0.00019
3.4 GHz	0.00456
3.8 GHz	0.00478
Others	0.17574
Total	0.31814

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.