

ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)¹, with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor² of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	12/05/2026	Time Survey completed:	14:03
Survey address:	Appleby CA16		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	US55240265	31/10/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1022	08/07/2025
Cabling	1.7m cable	1405	08/07/2025

¹ <https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf>

² The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at six locations and are presented in the following pages of this report.



Location 1

Measurement time:	13:00
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00853
174-230 MHz	0.00774
470-694 MHz	0.00601
700 MHz	0.01551
800 MHz	0.01039
900 MHz	0.00234
1400 MHz	0.00147
1800 MHz	0.00082
1900 MHz	0.00011
2100 MHz	0.00527
2300 MHz	0.00025
2600 MHz TDD	0.00026
2600 MHz FDD	0.00012
3.4 GHz	0.00102
3.8 GHz	0.00237
Others	0.10249
Total	0.16471

Location 2

Measurement time:	13:07
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00899
174-230 MHz	0.00788
470-694 MHz	0.00612
700 MHz	0.00392
800 MHz	0.00614
900 MHz	0.00106
1400 MHz	0.00051
1800 MHz	0.00147
1900 MHz	0.00011
2100 MHz	0.00730
2300 MHz	0.00026
2600 MHz TDD	0.00026
2600 MHz FDD	0.00013
3.4 GHz	0.00103
3.8 GHz	0.00243
Others	0.10507
Total	0.15268

Location 3

Measurement time:	13:16
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00904
174-230 MHz	0.00822
470-694 MHz	0.00633
700 MHz	0.00312
800 MHz	0.00554
900 MHz	0.00131
1400 MHz	0.00046
1800 MHz	0.00146
1900 MHz	0.00011
2100 MHz	0.00714
2300 MHz	0.00027
2600 MHz TDD	0.00027
2600 MHz FDD	0.00013
3.4 GHz	0.00110
3.8 GHz	0.00255
Others	0.10792
Total	0.15498

Location 4

Measurement time:	13:25
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00915
174-230 MHz	0.00843
470-694 MHz	0.00658
700 MHz	0.00133
800 MHz	0.00279
900 MHz	0.00093
1400 MHz	0.00039
1800 MHz	0.00096
1900 MHz	0.00012
2100 MHz	0.00077
2300 MHz	0.00028
2600 MHz TDD	0.00028
2600 MHz FDD	0.00014
3.4 GHz	0.00114
3.8 GHz	0.00268
Others	0.11166
Total	0.14761

Location 5

Measurement time:	13:48
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00949
174-230 MHz	0.00867
470-694 MHz	0.00677
700 MHz	0.01129
800 MHz	0.02083
900 MHz	0.00866
1400 MHz	0.00193
1800 MHz	0.00155
1900 MHz	0.00012
2100 MHz	0.00191
2300 MHz	0.00029
2600 MHz TDD	0.00030
2600 MHz FDD	0.00015
3.4 GHz	0.00129
3.8 GHz	0.00282
Others	0.11713
Total	0.19321

Location 6

Measurement time:	13:57
Frequency band	Percentage of the ICNIRP reference levels for general public exposure
87.5-108 MHz	0.00965
174-230 MHz	0.00879
470-694 MHz	0.00687
700 MHz	0.01193
800 MHz	0.01050
900 MHz	0.00197
1400 MHz	0.00074
1800 MHz	0.00073
1900 MHz	0.00013
2100 MHz	0.00633
2300 MHz	0.00030
2600 MHz TDD	0.00030
2600 MHz FDD	0.00015
3.4 GHz	0.00125
3.8 GHz	0.00285
Others	0.11790
Total	0.18039

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.