ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)[1], with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor[2] of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	20/05/2026	**Time Survey completed:**	12:09
Survey address:	Bristol_BS13		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072612	28/10/2025
Probe	Agos Aria-6000 Antenna	1117	08/07/2025
Cabling	1.7m cable	1460	20/11/2025

[1] https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

[2] The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	11:21
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	5.82228
174-230 MHz	0.01009
470-694 MHz	0.01040
700 MHz	0.02995
800 MHz	0.02168
900 MHz	0.00576
1400 MHz	0.00286
1800 MHz	0.00195
1900 MHz	0.00019
2100 MHz	0.00320
2300 MHz	0.00037
2600 MHz TDD	0.00042
2600 MHz FDD	0.00062
3.4 GHz	0.01002
3.8 GHz	0.00530
Others	0.25447
Total	**6.17956**

Location 2

Measurement time:	11:34
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.06209
174-230 MHz	0.01079
470-694 MHz	0.00914
700 MHz	0.03091
800 MHz	0.06112
900 MHz	0.00728
1400 MHz	0.02828
1800 MHz	0.04425
1900 MHz	0.00020
2100 MHz	0.03493
2300 MHz	0.00040
2600 MHz TDD	0.00205
2600 MHz FDD	0.01281
3.4 GHz	0.01571
3.8 GHz	0.00588
Others	0.14917
Total	**0.47502**

Location 3

Measurement time:	11:43
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	1.11057
174-230 MHz	0.01101
470-694 MHz	0.00974
700 MHz	0.05509
800 MHz	0.05036
900 MHz	0.00768
1400 MHz	0.02320
1800 MHz	0.01267
1900 MHz	0.00021
2100 MHz	0.01981
2300 MHz	0.00041
2600 MHz TDD	0.00113
2600 MHz FDD	0.00122
3.4 GHz	0.00346
3.8 GHz	0.00535
Others	0.18161
Total	**1.49352**

Location 4

Measurement time:	11:52
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.62399
174-230 MHz	0.01113
470-694 MHz	0.01457
700 MHz	0.01110
800 MHz	0.02421
900 MHz	0.01985
1400 MHz	0.00226
1800 MHz	0.00142
1900 MHz	0.00021
2100 MHz	0.00352
2300 MHz	0.00041
2600 MHz TDD	0.00038
2600 MHz FDD	0.00052
3.4 GHz	0.00372
3.8 GHz	0.00536
Others	0.17384
Total	**0.89648**

Location 5

Measurement time:	12:03
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	6.31998
174-230 MHz	0.01122
470-694 MHz	0.01065
700 MHz	0.02634
800 MHz	0.02269
900 MHz	0.00491
1400 MHz	0.00289
1800 MHz	0.00176
1900 MHz	0.00021
2100 MHz	0.00401
2300 MHz	0.00042
2600 MHz TDD	0.00041
2600 MHz FDD	0.00079
3.4 GHz	0.01426
3.8 GHz	0.00586
Others	0.28820
Total	**6.71460**

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.