ICNIRP Measurement Report

This report presents the results of measurements of electromagnetic field emission levels in the vicinity of mobile base stations. Results are presented as percentages of the power density reference levels for general public exposure in the 1998 edition of the Guidelines published by the International Commission on Non-Ionizing Radiation Protection (ICNIRP)[1], with figures provided for individual frequency bands used for base station (downlink) transmissions as well as an overall figure for all other frequency bands between 30 MHz to 6 GHz. The total percentage equals the sum of all individual percentages.

The power density reference levels in the ICNIRP Guidelines are the root mean square (rms) values averaged over six minutes. In this report, we have measured the average E-field strength over a six-minute period in each measurement location.

We have applied a measurement threshold of 3dB above the system noise floor[2] of the measurement equipment, below which any E-field strength levels measured are deemed not sufficiently above the system noise floor to be valid. In the results tables below, measurement results are shown to a precision of four decimal places. Results which are not sufficiently above the system noise floor to record as a valid measurement are shown as a dash (-). Results which are too small to register to four decimal places are shown as 0.0000%.

Date of Survey:	07/05/2026	**Time Survey completed:**	15:28
Survey address:	Parkhill DH6		

Measurement equipment		Serial number	Calibration Date
Meter	Keysight Fieldfox N9915A Spectrum Analyser	MY56072594	25/11/2025
Probe	Agos Aria-6000 Antenna	ARIA-6000-1156	08/07/2025
Cabling	1.7m cable	1378	08/07/2025

[1] https://www.icnirp.org/cms/upload/publications/ICNIRPemfgdl.pdf

[2] The noise floor of the measurement equipment is the level of background noise that is present before detecting any external signals. In other words, it indicates the absolute minimum level of detectable signals.

Broadcast bands covered by this report

Frequency Band	Frequency Range	Technology*
	87.5-108 MHz	FM Radio
	174-230 MHz	DAB
	470-694 MHz	Digital TV

Mobile bands covered by this report

Frequency Band	Frequency Range	Technology*
700 MHz	738-788 MHz	4G, 5G
800 MHz	791-821 MHz	4G
900 MHz	925-960 MHz	2G, 3G, 4G
1400 MHz	1452-1492 MHz	4G (Supplementary downlink)
1800 MHz	1805-1880 MHz	2G, 4G
1900 MHz	1900-1920 MHz	4G
2100 MHz	2110-2170 MHz	3G, 4G
2300 MHz	2350-2390 MHz	4G
2600 MHz TDD	2570-2620 MHz	4G
2600 MHz FDD	2620-2690 MHz	4G
3.4 GHz	3410-3680 MHz	5G, 4G
3.8 GHz	3680-4200 MHz	Various
Others**		

** This is an indication of the type of technologies typically deployed in these bands; not all frequency bands and technologies may be in use at all locations. ** All other frequencies between 30 MHz and 6 GHz.*

Survey locations

The survey was conducted within the area shown in the map below. Measurements were taken at five locations and are presented in the following pages of this report.



Location 1

Measurement time:	14:28
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01306
174-230 MHz	0.01497
470-694 MHz	0.01133
700 MHz	0.00284
800 MHz	0.02702
900 MHz	0.01859
1400 MHz	0.00056
1800 MHz	0.00743
1900 MHz	0.00027
2100 MHz	0.00310
2300 MHz	0.00180
2600 MHz TDD	0.00053
2600 MHz FDD	0.00028
3.4 GHz	0.00319
3.8 GHz	0.00812
Others	0.20575
Total	**0.31885**

Location 2

Measurement time:	14:36
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01251
174-230 MHz	0.01458
470-694 MHz	0.01109
700 MHz	0.00331
800 MHz	0.02746
900 MHz	0.01629
1400 MHz	0.00055
1800 MHz	0.00365
1900 MHz	0.00026
2100 MHz	0.00338
2300 MHz	0.00158
2600 MHz TDD	0.00051
2600 MHz FDD	0.00027
3.4 GHz	0.00309
3.8 GHz	0.00912
Others	0.20054
Total	**0.30821**

Location 3

Measurement time:	14:43
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01222
174-230 MHz	0.01417
470-694 MHz	0.01098
700 MHz	0.00258
800 MHz	0.02243
900 MHz	0.02663
1400 MHz	0.00054
1800 MHz	0.00480
1900 MHz	0.00026
2100 MHz	0.00342
2300 MHz	0.00663
2600 MHz TDD	0.00051
2600 MHz FDD	0.00027
3.4 GHz	0.00298
3.8 GHz	0.00745
Others	0.19453
Total	**0.31041**

Location 4

Measurement time:	14:54
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01206
174-230 MHz	0.01376
470-694 MHz	0.01050
700 MHz	0.00248
800 MHz	0.03288
900 MHz	0.03694
1400 MHz	0.00052
1800 MHz	0.00473
1900 MHz	0.00025
2100 MHz	0.00409
2300 MHz	0.00165
2600 MHz TDD	0.00048
2600 MHz FDD	0.00026
3.4 GHz	0.00287
3.8 GHz	0.00704
Others	0.18793
Total	**0.31844**

Location 5

Measurement time:	15:22
Frequency band	**Percentage of the ICNIRP reference levels for general public exposure**
87.5-108 MHz	0.01063
174-230 MHz	0.01180
470-694 MHz	0.00937
700 MHz	0.00199
800 MHz	0.01263
900 MHz	0.01009
1400 MHz	0.00045
1800 MHz	0.00104
1900 MHz	0.00021
2100 MHz	0.00273
2300 MHz	0.00123
2600 MHz TDD	0.00041
2600 MHz FDD	0.00021
3.4 GHz	0.00238
3.8 GHz	0.00605
Others	0.15863
Total	**0.22985**

Disclaimer: The results detailed in this report apply only to the tests made at the reported time, using the test equipment detailed. They do not indicate that on another date an identical set of results would be achieved, due to changes in local environmental conditions or other factors which may or may not have an effect on the measurement results obtained at that future time.